RHODESHADE
Solar Control Materials.

SiGr07

Film type

Shade Film | Article No. SF1100

8%	93%	57%	0.32
Visible light transmission[1]	UV rejection[1]	Total solar Reflection[1]	SHGC / g-value [2]

Description and Application

SiGr07 provides the highest daylight transmission within the range while maintaining clear outward views. At the same time, it offers effective glare protection and helps reduce solar heat gain. Its embossed and pleated surface ensures dimensional stability and a taut, refined appearance within the shading system.

SiGr07 is particularly suitable for bright, daylight-oriented spaces such as reception areas, meeting rooms and workstations near glazing, where natural light and outward visibility should be preserved while reducing screen glare.

FEATURES

Application	Indoor blinds
Color outside/inside	silver/gray
SC – Shading Coefficient[2]	0.37
Colour Rendering Index	90

[1] Tested to DIN EN 14500:2001-09 and DIN EN 410:2011-04 by accredited laboratory STFI Chemnitz.
[2] Calculated according to ISO 52022-3 using 4 mm single glazing.
Other values: Manufacturer´s specifications.
Product-related fluctuations and changes are reserved.

RHODETEC GmbH
Annaberger Str. 73 | 09111 Chemnitz
Germany
T: +49 371 270 96 720 | info@rhodetec.de
www.rhodetec.de
© 2026

RHODESHADE is a brand of: RHODETEC